

**PC Hardware Minimum Requirements for Eurosystem, and/or MAHA Products**  
**Valid from August 2010**

**MAHA Minimum Requirements for Hardware**

Operating system	Windows XP with Service pack 3 Windows Vista (32-Bit) for EUROSYSYSTEM V7.00.015 or later Windows 7 (32 Bit) for EUROSYSYSTEM V7.10.001 or later Windows 7 (64 Bit) for EUROSYSYSTEM V7.20.010 or later
CPU	Processor > 1.6 GHz frequency Recommended: Intel or similar AMD Products
Hard disk	1 GB free memory space
Graphic card	Resolution 1024 x 768 with 24 bit color depth (True-Color)
RAM	512 MB (Windows 7, Vista 1 GB)
Drives	DVD-ROM
Interfaces:	2 free USB interfaces

***General Information:***

**All passwords as well as administrator rights must be available at the time of the installation.**

If the tester is used with multiple work stations, a TCP/IP network must be available.

For external devices which are connected via an RS232 interface, an RS 232 interface must be available.

PC speciality stores offer a wide range of adapters for use from USB to RS232. There is, however, no standard guarantee that every adapter will function on the RS232 interfaces. For this reason, MAHA offers adapters with the order number VZ 910140 which have been tested on MAHA products.

When exchanging old computers with PC-LON cards (ISA slot), be aware that new computers no longer have ISA slots. For new computers that means that a LON-USB card (VZ 912033) is needed for the connection to the test lane.