

LIFTING TECHNOLOGY FOUR POST LIFT

CARLIFT II 4.0 W
VP 251114



CARLIFT II 4.0 W VP 251114

The four post CARLIFT II 4.0 W lifts vehicles of up to 4.0 t. Its runway, which is finely adjustable independent of the cross beam, enables high-precision wheel alignment. The extra reinforced plates welded onto the runway guarantee optimum stability. The special runway profile and its reinforced cross beams ensure high flexural resistance.

PRODUCT DETAILS/ACCESSORIES

Description:

- Four post lift with electro-hydraulic drive unit for surface mounting
- Precision wheel alignment design
- Special runway profile and reinforced crossbeams for high flexural resistance and long-term stability
- Torsion-free, high-precision fine adjustment of the platforms to the crossbar, resulting in perfect conditioning for wheel alignment
- Extra reinforcement plates welded onto runways for optimum stability
- Large runway width for all vehicle track widths
- Runways equipped with pre-integrated guide rail for axle lift
- Lowering device for chassis alignment included as standard, with precision-adjustable lock ladder and electromagnetically operated latches

- Low travel height for easy drive on
- Emergency DOWN feature in case of power failure
- Paint: high-quality powder coating:
 - Window Grey, RAL 7040 (Columns)
 - Anthracite Grey, RAL 7016 (Runways, Runway structures, Drive-on ramps, Traverses)

Scope of delivery:

- Four-post lift, Type CARLIFT II 4.0 W
- Operating box with control and hydraulic power unit
- Lockable main switch
- Settling device for wheel alignment
- 2 pieces drive-on ramps, 2 pieces roll bar
- Operating manual and inspection log book
- EC Declaration of Conformity CE
- Transport packaging

TECHNICAL DATA

Load capacity CE	4000 kg
Max. lifting height	1995 mm
Lifting /lowering time (depends on load)	approx. 30/30 s
Total dimensions (L x W)	5790 x 3480 mm
Drive-on height	175 mm
Drive-on height with wheel-free jack	175 mm
Drive-on height with setup for wheel alignment	225 mm
Drive-on height with setup for wheel alignment and wheel-free jack	225 mm
Platform dimensions (L (>>) W)	4400 x 630 mm
Platform length, optional	4800 mm
Column width clearance	2900 mm
Driving platform clearance	950 mm
Drive power	2.2 kW

LIFTING TECHNOLOGY FOUR POST LIFT

CARLIFT II 4.0 W
VP 251114



TECHNICAL DATA

Power supply	3/N/PE 400 V 50 Hz
Fuse gG	16 A
Weight	1500 kg
Hydraulic oil volume (not included)	10 l
Packaging dimensions (L x W x H)	4400 x 800 x 1200 mm

ACCESSORIES

VZ 990432	LED Illuminant, 2 pcs (1 pcs per each Runway)	VZ 975618	Set of compensating plates for turntables - length 450/500 mm (plain sheet, 4.4 m runway)
VZ 990433	LED Illuminant, 4 pcs (2 pcs per each Runway)	VZ 975619	Set of compensating plates for turntables - length 450/500 mm (plain sheet, 4.8 m runway)
VZ 971329	Extended Driving Platforms 4800 mm - Extra Charge	VZ 975620	Set of compensating plates for turntables - length 450/500 mm (plain sheet, 4.4 m runway)
VZ 990449	Mains power supply 3x230V, 50Hz -Extra charge-	VZ 975621	Set of compensating plates for turntables - length 450/500 mm (plain sheet, 4.8 m runway)
VZ 971302	Inground set (drive over capable) consisting of short flaps (4)-without extra charge	VZ 975027	Aluminium Covers for Sliding Plates (2 pcs.)
VZ 975617	Compressed-air quick coupler installed to runway, drive-on and drive-off side (2 pcs)	VZ 975653	Compensating Plates for Level Adaptation of Wheel-Free Jack (4,4 m Runways)
VZ 975181	Compressed-Air Servicing Unit with Fastening Angle (0 - 10 bar)	VZ 975667	Compensating Plates for Level Adaptation of Wheel-Free Jack (4,8 m Runways)
VZ 990029	Light Barrier Safety Device to avoid Contact with Ceiling	SUPPLEMENTARY CHARGES	
VZ 971331	Exit Flaps enable Vehicles to drive over Lift	VT 998199	Internal transport -SOUTHFour-post lift bis 5.5 t
VZ 971503	Extended Approach Ramps (2 pcs.) L = 1500 mm appr. angel 7° -Extra Charge-	VT 998200	Internal transport -NORTHFour-post lift bis 5.5 t
VZ 970112	Wheel-Free Jack 3.5 for Four-Post-Lift 4,0/5,0t	VM 995662	Montagekosten Vier-SäulenHebebühne mit 4000 kg Traglast
VZ 975069	Plastic Chocks (4 pcs.) (47 x 132 x 340 mm)	VM 996072	Install. Charges f. Ceiling Light Barrier -T(>>)>M Basis
VZ 975074	Hard Rubber Blocks, Plug-in Type (4 pcs.) 120 x 100 x 50 mm	VM 995087	Levelling of Scissors-Lift/ Four Post Lift
VZ 970027	Sliding Plates (2 pcs.) 'Long Version' LxWxH: 1465 x 570 x 50 mm	VM 999035	Hydraulic Oil (HLP-D 22) per Litre -NET PRICE
VZ 975026	Sliding Plates (2 pcs.) LxWxH: 1060 x 570 x 50 mm	VM 999014	Hydraulic Oil, Biodegradable (HLP 32), per litre -NET
VZ 971316	Sliding Plates Precision (2 pcs.) LxWxH: 1150x600x50 mm	VM 995661	Assembly Material for Four-Post Lift up to 5000 kg lifting cap.