


VEHICLE TESTING TECHNOLOGY SIDE-SLIP TESTER

C_MINC 2.5
VP 220015



C_MINC 2.5 VP 220015

The side-slip tester MINC-PROFI ensures that the axle geometry is inspected within seconds once the test vehicle passes over it as well as a fully automatic evaluation of the deviation in m/km. The display of the measured values is via the web client of the CONNECT series.

PRODUCT DETAILS/ACCESSORIES

Description:

Side-slip tester, checks the axle geometry within seconds while passed over by vehicle up to 2.5 t axle load

Specially suitable for car reception and diagnostic test lanes

Fully automatic evaluation of deviation in m/km

In combination with CONNECT Web client:
Automatic display on respective terminal device

(smart device, PC,) when vehicle drives onto tester,
including evaluation in m/km

Design:

- Side-slip tester C_MINC 2.5
- Self-supporting frame with movable test plate incl. vulcanised rubber pad
- High-quality powder coating: anthracite grey, RAL 7016

Scope of delivery:

- Side-slip tester C_MINC 2.5 floor assembly
- Prepared for connection to CONNECT test lane
- Plug-in cable harness with 3 m total length for connection with C_MBT floor assembly

TECHNICAL DATA

Axle load	2500 kg
Measurement range	+/- 20 m/km
Test speed	5 - 7 km/h
Floor assembly dimensions (H x W x L)	80 x 1020 x 460 mm

ACCESSORIES

VZ 935307 Cable harness extension 10 m for C_MINC series

SUPPLEMENTARY CHARGES

VT 998265 Transport Werkverkehr -SÜDRadlaufftester PKW

VT 998266 Transport Werkverkehr -NORDRadlaufftester PKW

VM 995031 Installation costs incl. briefing and calibration
MINC up to 4.0 t axle load